



International Plywood

Product Information - Last Updated in April 2021

Product Code 5060003110257

2440x1220x5.5mm ASIA PLY A1 PEFC™ Certified Malaysian Hardwood Plywood

This product is suitable for NON - STRUCTURAL use

| | | | | | |
|------------------------|----------------------------|-----------------|-----------------|--------------------|----------------------|
| Length | 2440mm | Width | 1220mm | Thickness | 5.50mm |
| Average Density | 600kg/m ³ | Pieces per Pack | 165 | Volume per Pack | 2.7010m ³ |
| Service Class | EN636-3 | Glue Bond | EN314-2 Class 3 | Formaldehyde Class | E1 |
| Country of Manufacture | Malaysia | | | | |
| Manufacturer | Asia Plywood - Malaysia | | | | |
| Environmental Status | PEFC™ Certified | | | | |
| FSC® Product Type | Not FSC® Certified | | | | |
| PEFC™ Product Type | 05000 (All Panel Products) | | | | |
| Product Grade | A1 Asia Plywood | | | | |
| Product Type | Hardwood Throughout | | | | |

Material Safety Data for Plywood and Wood Based Panels:

Wood-based panels can be bulky and heavy and this needs to be considered when manual handling is performed. Further information can be obtained from the HSE website. <http://www.hse.gov.uk/pubns/indg318.htm>

Machining and processing (cutting or sanding for example) of wood-based panels will produce dust which can cause irritation to eyes and throat. The use of protective goggles and face-masks and suitable dust extraction equipment is therefore recommended. Further information can be obtained from the HSE website. <http://www.hse.gov.uk/woodworking/wooddust.htm>

Wood splinters can cause irritation or infection if they enter the skin - wearing suitable gloves is therefore recommended to protect the hands.

Under certain circumstances the release of small quantities of formaldehyde gas from wood-based panels containing formaldehyde based adhesives can cause irritation of the eyes and throat. Always ensure adequate ventilation is available in areas where products are stored or processed.

All wood-based products are flammable - store them in a cool, dry, well ventilated place away from sources of heat, flames or sparks.

**All plywood used externally should be both edge-sealed and treated with a suitable wood preservative
Please contact our Sales Office for further information**

INTERNATIONAL PLYWOOD (IMPORTERS) LTD

Innsworth Technology Park, Innsworth Lane, Gloucester, GL3 1DL, England VAT Reg. No: GB 348 1272 56
Telephone: 00 44 (0) 1452 731493 Fax: 00 44 (0) 1452 731497 Accounts Enquiries: 00 44 (0) 1452 733606
Email: info@plywooduk.com Website: www.plywooduk.com

This document was produced on 06/04/2021 at 15:08:42